


APPLICATION: GENERAL PURPOSE AMPLIFY APPLICATIONS,
WITCHING APPLICATION.

MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Collector-base voltage	V _{CBO}	-40	V
Collector-emitter voltage	V _{CEO}	-32	V
Emitter-base voltage	V _{EBO}	-5	V
Collector current	I _C	-500	mA
Collector Power Dissipation	P _C	200	mW
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{stg}	-55~150	°C

SOT-23



1.Base 2 .Emitter 3 .Collector

ELECTRICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
DC Current Gain	h _{FE}	82		820		V _{CE} = -6V, I _C = -1mA
Collector Cut-off Current	I _{CBO}			-1	μA	V _{CB} = -50V, I _E =0
Emitter Cut-off Current	I _{EBO}			-1	μA	V _{EB} = -5V, I _C =0
Collector-Base Breakdown Voltage	BV _{CBO}	-40			V	I _C = -0.1mA, I _E =0
Collector-Emitter Breakdown Voltage	BV _{CEO}	-32			V	I _C = -1mA, I _B =0
Emitter-Base Breakdown Voltage	BV _{EBO}	-5			V	I _E = -0.1mA, I _C =0
Collector-Emitter Saturation Voltage	V _{CE(sat)}			-0.4	V	I _C = -100mA, I _B = -10mA
Gain bandwidth product	f _T	100	200		MHz	I _C = -2mA, V _{CE} = -10V
Common Base Output Capacitance	C _{ob}		7		PF	V _{CB} = -10V, I _E =0, f = 1MHz

h_{FE} Classification And Marking

Print Mark 36P

Classification P

h_{FE} 82~180