


APPLICATION: General Purpose Amplifier Application.

MAXIMUM RATING (Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Collector-base voltage	V _{CBO}	60	V
Collector-emitter voltage	V _{CEO}	30	V
Emitter-base voltage	V _{EBO}	5	V
Collector current	I _C	600	mA
Collector Power Dissipation	P _C	600	mW
Junction Temperature	T _J	150	°C
Storage Temperature Range	T _{stg}	- 55~150	°C



ELECTRICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Common Emitter DC Current Gain	h _{FE}	100		300		V _{CE} = 10V, I _C = 150mA
Collector Cut-off Current	I _{CBO}			0.1	μA	V _{CB} = 50 V, I _E =0
Emitter Cut-off Current	I _{EBO}			0.1	μA	V _{EB} = 5 V, I _C =0
Collector-Base Breakdown Voltage	BV _{CBO}	60			V	I _C = 0.1mA, I _E =0
Collector-Emitter Breakdown Voltage	BV _{CEO}	30			V	I _C = 1 mA, I _B =0
Emitter-Base Breakdown Voltage	BV _{EBO}	5			V	I _E = 0.1mA, I _C =0
Collector-Emitter Saturation Voltage	V _{CE(sat)}			0.4	V	I _C = 150 mA, I _B = 15 mA
Base-Emitter Saturation Voltage	V _{BE(sat)}			1.3	V	I _C = 150 mA, I _B = 15 mA
Gain bandwidth product	f _T	250			MHz	I _C = 20 mA, V _{CE} = 20 V
Common Base Output Capacitance	C _{ob}			8	PF	V _{CB} = 10 V, I _E =0, f = 1 MHz
Turn on Time	t _{on}			35	dB	V _{CC} = 30 V, I _C = 150 mA, I _{B1} =15mA
Turn off Time	t _{off}			285	dB	V _{CC} = 30 V, I _C = 150 mA, I _{B1} =I _{B2} =15mA

h_{FE} Classification

Classification

h_{FE} 100 ~ 300